

# SPECIFICATION

Model	PDS4208W-B/PDS4209U-B		
Screen size	42" wide screen (92.0 cm (W) x 51.8 cm (H) x 105.6 cm (Diagonal))		
Aspect ratio	16:9 (wide)		
Weight	31.5 kg		
Outer dimensions	103.5 (W) x 64.0 (H) x 8.5 (D) cm		
Power supply	PDS4208W-B: 100-240 VAC 50/60 Hz PDS4209U-B: 120 VAC 50/60 Hz		
Power consumption	PDS4208W-B: 3.7 A (800 VA: Power ON, instantaneous power when outputting image) PDS4209U-B: 3.2 A (800 VA: Power ON, instantaneous power when outputting image)		
Screen dimensions	92.0 (W) x 51.8 (H) cm		
Number of pixels	852 (H) x 480 (V)		
Display modes	Video, S-video input:	Normal/Wide1/Wide2/Zoom1/Zoom2	
	Component video input:	Normal/Wide1/Wide2/Zoom1/Zoom2	
	RGB input:	Normal/Wide/Zoom	
Colors	16.77 million (for each of 256 RGB gradations)		
External equipment terminals			
Video input terminals	Video image input	1 BNC terminal	1 V <sub>p-p</sub> /75 Ω
	S-video image input	1 S terminal	Y: 1 V <sub>p-p</sub> /75 Ω C: 0.3 V <sub>p-p</sub> /75 Ω
	Component video input (color difference input)	3 BNC terminals	Y: 1 V <sub>p-p</sub> /75 Ω Pb/B-Y: 0.7 V <sub>p-p</sub> /75 Ω Pr/R-Y: 0.7 V <sub>p-p</sub> /75 Ω
Applicable systems	NTSC/PAL/SECAM/4.43NTSC		
PC input terminal	RGB input terminal	mD-sub, 3 rows, 15-pin Image signal: 0.7 V <sub>p-p</sub> /75 Ω Synchronization signal: TTL level or 0.3 V <sub>p-p</sub> /75 Ω	
Control terminal	1 RS-232C connector (D-sub 9-pin)		
Operating conditions	Temperature: 0 to 40°C Humidity: 20 to 90%		
Accessories	1 remote control, 2AA batteries, 1 instruction manual, 2 safety brackets of each type (2 types), 2 screws of each type (2 types), 2 ferrite cores, 2 wire clampers, 2 cable clampers, 1 power cable		